



PIN OUT

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
SHELL	SHELL(DRAIN WIRE)

APPROVED BY _____

COMPANY: _____

PURCHASING/ENGINEER: _____

DATE: _____

- NOTE:
- 1.CABLE:28AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE (BG-02) PVC JACKET Ø5.0±0.15mm.
 - 2.CONNECTOR:
 P1: D-SUB 9PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS;PBT BLACK INSULATION. GOLD PLATED SHELL.
 P2: D-SUB 9PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS.PBT BLACK INSULATION. GOLD PLATED SHELL.
 - 3.THUMB SCREW TO BE MOLDED BEIGE.
 - 4.ALL HOOD: MOLDED BEIGE PVC.UL94V-0.
 - 5.TESTING:100% ELECTRICAL TESTING.



A	INITIAL RELEASE		06/03/19	
REV	DESCRIPTION OF CHANGE		DATE	
TOLERANCE INCHES M/M			Tsukasa Electronics Co.,Ltd	
.X	.015	.30	SCALE	NONE
.XX	.010	.10	UNIT	MM
.XXX	.005	.05	SHEET	1/1
DRAWN BY	bobo		DATE	06/03/19
CHECK BY			DWG NO.	REV A
APPD BY			TITLE	DB9M TO DB9F
			PART NO.	TKSD-20190531-2000MM